





RECOMMENDED PCB LAYOUT
(THICKNESS=1.6)

MATERIALS:





1. Housing: LCP (UL94 V-0), Black
2. Cover: LCP (UL94 V-0), Black
3. Contact: Brass
4. Shell: Brass

FINISH:

1. Contact: Gold Flash Plated On Contact Area
Tin Plated On Solderails
Nickel Under Plated Over All
2. Shell: Nickel Plated

SPECIFICATION:

1. Current: 0.5A
2. Voltage: 40V RMS
3. Dielectric Withstanding Voltage: 500V AC/60S
4. Contact Resistance: 30 mΩ Max.
5. Insulation Resistance: 100MΩ Min. At 500V DC;
6. Operating Temperature: -25°C to +85°C



僅供參考

XIAN YI PRECISION CO., LTD.
祥益精密股份有限公司

TITLE /品名: DP 90度 SMD 直腳無柱 銅殼

核准發行章

PART NO /料號: DSF20U-11BN-28R0




APPROVE /核準

CHECKED / 審查

DRAWING / 繪圖

DRAWING NO /圖號

UNIT / 單位



SHEET 1 OF 1

	1.0
NO.	REV /版本

1.0

EV / 片

圖面僅供參考, 實際尺寸以承認圖為主

2025/12/19

修訂內容

日期