








RECOMMENDED PCB LAYOUT



MATERIALS:

1. Housing: LCP (UL94 V-0), Black
2. Contact: Brass
3. Shell: Brass

FINISH:

1. Contact: Gold Flash Plated On Contact Area
Tin Plated On Solderails
Nickel Under Plated Over All
2. Shell: Nickel Plated

SPECIFICATIONS:

1. Current Rating: 0.5 A
2. Voltage Rating: 40 V
3. Contact Resistance: 30 mΩ Max,
4. Insulation Resistance: 100 MΩ Min. At 500V DC.
5. Dielectric Withstanding Voltage: 500V AC/60S
6. Operating Temperature: -25°C To +85°C

僅供參考

XIAN YI PRECISION CO., LTD.

祥益精密股份有限公司

TITLE / 品名: HDMI A/F 90度 三排DIP(有柱) 前腳外撐 帶鎖片(H=6.2)

PART NO / 料號: HAF19L-11BN-G1P0

核準發行章

APPROVE / 核準	CHECKED / 審查	DRAWING / 繪圖	DRAWING NO / 圖號
<i>Kin</i>	<i>Chenrong</i>	<i>Chenrong</i>	A-MI-011-00

UNIT / 單位	☉	◁
mm	SHEET 1	OF 1

NO.	REV / 版本	修訂內容	日期
△			
△			
△	1.0	圖面僅供參考, 實際尺寸以承認圖為主	2025/12/19