




MATERIALS:

1. Housing: PBT (UL 94V-0), Black / Blue
2. Connecting Seat: PA66 (UL 94V-0), Black
3. Contacts: Brass
4. Shell: SPCC
5. Rivet: Copper Alloy(Lead $\leq$ 40000PPM)
6. Board Lock: Brass
7. L Bracket: SPCC
8. Screw: SPCC
Or Copper Alloy(Lead $\leq$ 40000PPM)

FINISH:

1. Contacts: Gold Flash Plated on Contact Area
Tin Plated on Solderails
Nickel Under Plated Over All
2. Shell: Nickel Plated
3. Rivet: Nickel Plated
4. Board Lock: Tin Plated
5. L Bracket: Nickel Plated
6. Screw: Nickel Plated

SPECIFICATION:

1. Current Rating: 2 Amp
2. Dielectric Withstanding Voltage: AC 500V For 1 minute
3. Insulation Resistance: 5000M Ω Min
4. Contact Resistance: 30m Ω Max.
5. Operating Temperature: -55°C to +105°C

XIAN YI PRECISION CO., LTD.
祥益精密股份有限公司

TITLE / 品名: VGA-15P母+VGA-15母(5.08) 90度 疊層 Dip Type (層距19.05)

PART NO / 料號: DC2122-1F1F-RXXXX

核準發行章

APPROVE / 核準

CHECKED / 審查

DRAWING / 繪圖

DRAWING NO / 圖號

UNIT / 單位

SHEET 1 OF 1

NO. REV / 版本

圖面僅供參考, 實際尺寸以承認圖為主

2025/12/19

修訂內容

日期