



- MATERIALS:**
- Housing: PBT (UL 94V-0), Black / Blue
 - Connecting Seat: PA66 (UL 94V-0), Black
 - Contacts: Brass
 - Shell: SPCC
 - Rivet: Copper Alloy(Lead ≤ 40000PPM)
 - Board Lock: Brass
 - L Bracket: SPCC
 - Screw: SPCC
Or Copper Alloy(Lead ≤ 40000PPM)

- FINISH:**
- Contacts: Gold Flash Plated on Contact Area
Tin Plated on Solderails
Nickel Under Plated Over All
 - Shell: Nickel Plated
 - Rivet: Nickel Plated
 - Board Lock: Tin Plated
 - L Bracket: Nickel Plated
 - Screw: Nickel Plated

- SPECIFICATION:**
- Current Rating: 2 Amp
 - Dielectric Withstanding Voltage: AC 500V For 1 minute
 - Insulation Resistance: 5000MΩ Min
 - Contact Resistance: 30mΩ Max.
 - Operating Temperature: -55°C to +105°C

鉚合鎖螺絲型

P.C.B. LAYOUT

鉚合型

僅供參考

XIAN YI PRECISION CO., LTD.
祥益精密股份有限公司

TITLE / 品名: VGA-15P母+VGA-15母(5.08) 90度 疊層 Dip Type (層距15.88)

PART NO / 料號: DC8122-1F1F-RXXXX

核準發行章

APPROVE / 核准	CHECKED / 審查	DRAWING / 繪圖	DRAWING NO / 圖號	UNIT / 單位	☉	X
<i>Kin</i>	<i>Chenrong</i>	<i>Chenrong</i>	K-2D-008-00	mm	SHEET 1 OF 1	

NO.	REV / 版本	圖面僅供參考, 實際尺寸以承認圖為主	2025/12/19
		修訂內容	日期

NO.	REV / 版本	圖面僅供參考, 實際尺寸以承認圖為主	2025/12/19
		修訂內容	日期